

Automatic Voltage Regulator



■ Specification

Model		NU-1200M	NU-2000M	NU-3000M	NU-4000M
Capacity	-17%~+21%	1.2KVA/960W	2KVA/1.6KW	220V:3KVA/2.4KW 110V:3KVA/1.8KW	220V:4KVA/3.2KW 110V:4KVA/2.4KW
	-23%~+30%	1.2KVA/720W	2KVA/1.2KW	3KVA/1.8KW	4KVA/2.4KW
Input	Normal Voltage	1 ϕ 2W 100/110/115/120VAC or 200/220/230/240VAC			
	Voltage Range	-23%~+30%			
	Frequency	47HZ~63HZ			
Output	Voltage Range	$\leq 5\%$			
	Outlets	Nema5-15r	4 outlets	6 outlets	Terminal+ 2 outlets
		Universal	2 outlets	2 outlets	x
		Schuko	2 outlets	2 outlets	x
	Efficiency	>97%(Full load)			
	Overload Capacity	200% for 5 seconds			
	Distortion	No Distortion(the same as input waveform)			
Power Factor	0.6~0.8				
Display	LED	Yes(normal、overheat、input low)			
	Output Voltmeter	Yes			
Protection	Output Delay on	Yes(output delay for 4 seconds)			
	Overload ,Short	Yes(Circuit Breaker)			
	I/P Hi ,I/P Low	Yes(Cut-off output)			
	Overheat	Yes(Cut-off output)			
	Surge	Yes(4500A,8/20us)			
	Zero Transfer	Yes			
Environment	Operation Temp.	0°C ~ 40°C			
	Relative Humidity	0%~95%(non-condensing)			
	Audible Noise	40dB(at 1 meter)			
Physical	Net Weight(kgs)	3.5	4.8	5.5	5.9
	Dimension(W*D*H)mm	94mm(W)*271mm(D)*172mm(H)			

● Specification is subjected to change without notice ◦

